

Common User Data

Machine Name: USA4320-448-WC5865
 IP Address: 13.243.33.24
 Machine Serial Number: EX9282549
 Fax Line1: 952-921-1414
 System Software Version: 071.190.103.35100
 Machine URL: http://13.243.33.24

Machine Profile

Machine Name: USA4320-448-WC5865
 Machine Serial Number: EX9282549
 Xerox Asset Tag:
 Customer Asset Tag:
 Service Phone Number:
 Customer Support Phone Number:
 Supplies Phone Number:
 System Administrator: System Administrator name not set
 Machine Location: USA 4320 Bloomington, MN

Machine Hardware

Fax Card: present
 Extended Fax Card: not present
 Fax Card Memory Size: 985 MB
 Foreign Interface Card: not present
 Net Controller RAM: 2048 MB
 Net Controller Disk Size: used=4555MB/total=160041MB
 EPC Memory Size: 512 MB
 Image Disk: present
 Finisher Type: Office Finisher (LCSS) with Hole Punch
 Finisher Punch: Present
 Finisher Folder: not present

General Setup

Low Power Mode Timer: 60 minutes
 Sleep Mode Timer: 120 minutes
 Energy Saver Mode: Job Activated
 SMart eSolutions: Enrolled
 SMart eSolutions Trans. Time: 21:05
 E-mail Alerts: Enabled
 Service Plan: Metered
 Startup Config Report: Enabled
 GMT Offset: -6.00

Software Versions

System Software: 071.190.103.35100
 Network Controller: 071.193.35110.LL
 User Interface: 071.193.35110
 Marking Engine: 096.046.000
 Copy Controller: 071.193.35110
 Document Feeder: 110.011.010
 Finisher: 003.057.000
 Fax: 003.010.032
 Copy Controller OS: 071.003.35110
 Network Controller OS: 071.003.35110
 Scanner: 002.071.000
 Software Upgrade: 190.116.00252

Machine Upgrades:

Last Successful Upgrade: Enabled
 December 23, 2013 11:24:34
 Scheduled Auto Upgrades: Disabled
 Auto Upgrade Start Time: Daily
 Auto Upgrade Server: 0.0.0.0:21

Connectivity Physical Connections

USB Settings

USB Connection Mode: Software Tools
 Print Timeout: 5 seconds

Wired:

Ethernet MAC Address: Enabled
 Ethernet Speed/Duplex Setting: 9c:93:4e:1b:7e:9d
 auto

Wireless:

SSID: Disabled
 Security Mode:
 Encryption Algorithm:
 Status:

Connectivity Protocols

NetWare:

Print Server Name: Disabled
 XRX9C934E1B7E9D
 NDS Tree: Xerox_DS_Tree
 NDS Context: Xerox_DS_Context
 NDS Server: 0.0.0.0
 Novell Filling Transport: IP
 IPX Frame Type: ethernet_auto
 IPX External Number:

AppleTalk:

Name: Disabled
 XRX9C934E1B7E9D
 Zone:

Connectivity Protocols (cont.)

TCP/IPV4:

Enabled
 IP Address: 13.243.33.24
 Subnet Mask: 255.255.255.0
 Router/Gateway: 13.243.33.1
 Automatic Addressing: STATIC
 DHCP Server: 13.135.134.15
 DHCP Lease Expiration: Mon Jul 1 10:59:41 2013 CDT
 BOOTP Broadcast: Disabled
 Self Assigned Address State: Enabled
 Self Assigned Address: 169.254.70.219

TCP/IPV6:

Link Local Address:
 Use Router Supplied Prefix: Enabled
 Stateless Global Address 1:
 Stateless Global Address 2: ::
 Manual Address:
 DHCP Addressing: Use DHCP as directed by a router
 DHCP Address:
 Default Gateway:

DNS Settings:

Requested Host Name: USA4320-445-WC5865
 Verified Host Name:
 Requested Domain Name: na.xerox.net
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registra... Disabled
 Primary DNS Server: 13.135.130.15
 Alternate DNS Server 1: 13.135.177.15
 Alternate DNS Server 2: 13.151.178.15
 Connection Timeout: 5
 Append Device Domain: Enabled
 Append Parent Domains: Disabled
 DNS Domain Search List: na.xerox.net.
 Prefer IPv6 DNS over IPv4: Disabled

HTTP:

Port Number: Enabled
 80
 Force Traffic over SSL: Yes
 Secure HTTP Port Number: 443
 Proxy Server: Enabled
 Proxy Server Address: proxywest.idns.xerox.com:8000
 IPP Network Path: https://13.243.33.24:443

SNMP

SNMP v1/v2: Enabled
 SNMP v3: Enabled

LPR/LPD:

Port Number: Disabled
 515
 PDL Switching: Disabled
 PDL Banner Override: Disabled

Raw IP Printing:

Port Number 1: Disabled
 9100
 Bidirectional: Disabled
 End of Job Timeout: 300
 PDL Switching: Disabled

LDAP

Primary LDAP Address: ldapsna.idns.xerox.com:389
 Alternate LDAP Address: ldapseu.idns.xerox.com:389
 Search Directory Root: DC=na,DC=xerox,DC=net
 Login Credentials: System
 SSL: Disabled
 LDAP Referrals: Disabled
 Query On: Surname and Given Name Fields

Address Book Filter State:

Disabled

Address Book Filter:

User ID Query Filter State:

Disabled

User ID Query Filter:

SMTP

SMTP Server: forwarder.mail.xerox.com:25
 E-mail Address: xerox.scan2email@xerox.com
 Max Message Size (KB): 10240
 Number of Fragments: 1
 Total Job Size (KB): 300000
 Job Splitting Boundary: Page Boundary
 Credentials for Auto E-mails: None
 Credentials for Walkup User: None

POP3

POP3 Server: 0.0.0.0:110
 Receipt of E-mail via POP3: Enabled
 Send Confirm on Request: Enabled
 Incoming E-mail cover sheet: Enabled



Connectivity Protocols (cont.)

NTP:
Primary Server: 0.0.0.0:123
Alternate Server: 0.0.0.0:123

SLP: Disabled

SSDP: Enabled

FTP: Passive

Web Services on Device:
WS-Discovery: Disabled
WS-Discovery Multicast: Enabled
WS-Print: Enabled
WS-Scan: Enabled

Web Services
Extensible Service Registration: Enabled
Scan Template Management: Enabled
Xerox Secure Access: Enabled
Session Data: Enabled
Scan Extensions: Enabled
Machine Configuration: Enabled
Authen. & Author. Config: Enabled

Services

Printing
Banner Sheet: Enabled
Sys/Start Job: Disabled
Error Sheets: Enabled
Paper Substitution: Enabled
Tray Priority: 3,1,2,4,5
Default Copies: 1
Default Job Type: Normal Print
Default Paper Size: x=8.50 inches, y=11.00 inches
Default Paper Color: White
Default 2 Sided Printing: 1 Sided
Default Output Tray: Top Tray
Default Output Color: Black & White
Default Collated Sets: Enabled
Default Stapling: No Staple
PostScript
Level: Installed
Version: 3
Image Quality: 3017.102
Toner Saver: Not Installed
XPS (XML Paper Specification)
Level: XPS 1.0
Version: XPS 1.0
Image Quality: Toner Saver

PCL
Version: 6
Pitch Size: 10.00
Point Size: 12.00
Font Name: Courier
Lines Per Page: 60

Embedded Fax: Installed/Displayed
Fax Line1: 952-921-1414
Fax Line2: -----

Internet Fax: Not Displayed
Delivery Confirm Timeout: 10800 seconds
Confirmation Sheet: Errors Only
Activity Report: Enabled
Accept Email with no Attach: Disabled

Server Fax: Not Displayed
Confirmation Sheet: Errors Only
Delay Start: Disabled
Repository Protocol: FTP
Repository Server: 0.0.0.0
Repository Document Path: /

Workflow Scanning: Displayed
Confirmation Sheet: Errors Only
Default Repository Protocol: FTP
Default Repository Server: 13.135.149.15:21
Default Repository Path: /InboxMFD
Default Repository Login Credentials: System
Alt1 Repository Protocol: FTP
Alt1 Repository Server: 0.0.0.0:21
Alt1 Repository Document Path: System
Alt1 Repository Login Credentials: FTP
Template Pool Protocol: 13.135.149.15:21
Template Pool Server: /TemplatePoolMFD/21da3454-47b2-43bb-98...

Services (cont.)

Email: Displayed
Default From Address: xerox.scan2email@xerox.com
Default From Name:
Confirmation Sheet:
Auto Send to Self:
E-mail Security:
Scan to Mailbox:
View Mailboxes by Default: Enabled
Storage Capacity (MB): 28161.48 MB
Storage Used (MB): 1602.60 MB
Cleanup of Public Folders: Enabled
Cleanup of Created Folders: Enabled
Cleanup Time: Hourly
Scan to Home: Enabled/Displayed
Friendly Name: Scan2Home
Template Name:
Auto Create Subdir: Enabled
Append User Name to Path: Enabled
Auto Create User Name Dir: Enabled
Scan To: Displayed
Print From: Displayed
Saved Jobs for Reprint: Enabled
Print From USB: Enabled
Print From Mailbox: Disabled

Accounting

Accounting Mode: None
Network Accounting: Disabled

Security

Authentication Configuration
Machine UI Authentication: Locally on the Device
Services Pathway: Unlocked
Job Status Pathway: Unlocked
Machine Status Pathway: Unlocked
Web UI Authentication: Locally on the Device
Authorization: Locally on the Device
Retrieve E-mail from LDAP: Enabled
Authentication Server: Disabled
Kerberos Primary Realm: 0.0.0.0:88
Kerberos Primary Address: 0.0.0.0:88
Kerberos Alt 1 Realm:
Kerberos Alt 1 Address:
SMB NT Domain:
SMB Alt 1 NT Domain:
NDS Default Tree:
NDS Default Context:
NDS Alt 1 Tree:
NDS Alt 1 Context:
Smartcard Ctrl Server:
Smartcard Ctrl Domain:
SmartCard OCSP URL:
Xerox Secure Access: Enabled
Secure Access Server: 0.0.0.0:443
Secure Access Path:
Audit Log: Enabled
IP Sec: Disabled
IP Filtering: Disabled
802.1x: Disabled
Authentication Method: EAP-MD5
Image Overwrite
Immediate: installed/disabled
Scheduled: Disabled
Scheduled Frequency: Monthly
Encryption
FIPS 140-2: Disabled
User Data Encryption: installed/enabled
McAfee Embedded Control
Enhanced Security: Enabled
Integrity Control: Disabled

Media Trays

Tray 1: Plain, White and Letter (8.5 x 11")
Tray 2: Plain, White and Letter (8.5 x 11")
Tray 3: Plain, White and A4 (210 x 297 mm)
Tray 4: Plain, White and A4 (210 x 297 mm)
Tray 5 (Bypass): Cardstock, White and x=5.98 inches, y=5.20...

Common User Data

Machine Name: USA4320-448-WC5865
 IP Address: 13.243.33.24
 Machine Serial Number: EX9282549
 Fax Line1: 952-921-1414
 System Software Version: 071.190.103.35100
 Machine URL: http://13.243.33.24

Machine Profile

Machine Name: USA4320-448-WC5865
 Machine Serial Number: EX9282549
 Xerox Asset Tag:
 Customer Asset Tag:
 Service Phone Number:
 Customer Support Phone Number:
 Supplies Phone Number:
 System Administrator:
 Machine Location: System Administrator name not set
 USA 4320 Bloomington, MN

Machine Hardware

Fax Card: present
 Extended Fax Card: not present
 Fax Card Memory Size: 985 MB
 Foreign Interface Card: not present
 Net Controller RAM: 2048 MB
 Net Controller Disk Size: used=4555MB/total=160041MB
 EPC Memory Size: 512 MB
 Image Disk: present
 Finisher Type: Office Finisher (LCSS) with Hole Punch
 Finisher Punch: Present
 Finisher Folder: not present

General Setup

Low Power Mode Timer: 60 minutes
 Sleep Mode Timer: 120 minutes
 Energy Saver Mode: Job Activated
 SMart eSolutions: Enrolled
 SMart eSolutions Trans. Time: 21:05
 E-mail Alerts: Enabled
 Service Plan: Metered
 Startup Config Report: Enabled
 GMT Offset: -6.00

Software Versions

System Software: 071.190.103.35100
 Network Controller: 071.193.35110.LL
 User Interface: 071.193.35110
 Marking Engine: 096.046.000
 Copy Controller: 071.193.35110
 Document Feeder: 110.011.010
 Finisher: 003.057.000
 Fax: 003.010.032
 Copy Controller OS: 071.003.35110
 Network Controller OS: 071.003.35110
 Scanner: 002.071.000
 Software Upgrade: 190.116.00252
Machine Upgrades:
 Last Successful Upgrade: Enabled
 December 23, 2013 11:24:34
 Scheduled Auto Upgrades: Disabled
 Auto Upgrade Start Time: Daily
 Auto Upgrade Server: 0.0.0.0:21

Connectivity Physical Connections

USB Settings

USB Connection Mode: Software Tools
 Print Timeout: 5 seconds

Wired:

Ethernet MAC Address: Enabled
 Ethernet Speed/Duplex Setting: 9c:93:4e:1b:7e:9d
 auto

Wireless:

SSID: Disabled
 Security Mode:
 Encryption Algorithm:
 Status:

Connectivity Protocols

NetWare:

Print Server Name: Disabled
 XRX9C934E1B7E9D
 NDS Tree: Xerox_DS_Tree
 NDS Context: Xerox_DS_Context
 NDS Server: 0.0.0.0
 Novell Filing Transport: IP
 IPX Frame Type: ethernet_auto
 IPX External Number:

AppleTalk:

Name: Disabled
 XRX9C934E1B7E9D
 Zone:

Connectivity Protocols (cont.)

TCP/IPv4:

IP Address: Enabled
 13.243.33.24
 Subnet Mask: 255.255.255.0
 Router/Gateway: 13.243.33.1
 Automatic Addressing: STATIC
 DHCP Server: 13.135.134.15
 DHCP Lease Expiration: Mon Jul 1 10:59:41 2013 CDT
 BOOTP Broadcast: Disabled
 Self Assigned Address State: Enabled
 Self Assigned Address: 169.254.70.219

TCP/IPv6:

Link Local Address:
 Use Router Supplied Prefix: Enabled
 Stateless Global Address 1:
 Stateless Global Address 2:
 Manual Address: ::
 DHCP Addressing: Use DHCP as directed by a router
 DHCP Address:
 Default Gateway:

DNS Settings:

Requested Host Name: USA4320-445-WC5865
 Verified Host Name:
 Requested Domain Name: na.xerox.net
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registra... Disabled
 Primary DNS Server: 13.135.130.15
 Alternate DNS Server 1: 13.135.177.15
 Alternate DNS Server 2: 13.151.178.15
 Connection Timeout: 5
 Append Device Domain: Enabled
 Append Parent Domains: Disabled
 DNS Domain Search List: na.xerox.net.
 Prefer IPv6 DNS over IPv4: Disabled
HTTP:
 Port Number: Enabled
 80
 Force Traffic over SSL: Yes
 Secure HTTP Port Number: 443
 Proxy Server: Enabled
 Proxy Server Address: proxywest.idns.xerox.com:8000
 IPP Network Path: https://13.243.33.24:443

SNMP

SNMP v1/v2: Enabled
 SNMP v3: Enabled

LPR/LPD:

Port Number: Disabled
 515
 PDL Switching: Disabled
 PDL Banner Override: Disabled

Raw IP Printing:

Port Number 1: Disabled
 9100
 Bidirectional: Disabled
 End of Job Timeout: 300
 PDL Switching: Disabled

LDAP

Primary LDAP Address: Idapsna.idns.xerox.com:389
 Alternate LDAP Address: Idapseu.idns.xerox.com:389
 Search Directory Root: DC=na,DC=xerox,DC=net
 Login Credentials: System
 SSL: Disabled
 LDAP Referrals: Disabled
 Query On: Surname and Given Name Fields
 Default Login Context:
 Address Book Filter State: Disabled
 Address Book Filter:
 User ID Query Filter State: Disabled
 User ID Query Filter:

SMTP

SMTP Server: forwarder.mail.xerox.com:25
 E-mail Address: xerox.scan2email@xerox.com
 Max Message Size (KB): 10240
 Number of Fragments: 1
 Total Job Size (KB): 300000
 Job Splitting Boundary: Page Boundary
 Credentials for Auto E-mails: None
 Credentials for Walkup User: None

POP3

POP3 Server: 0.0.0.0:110
 Receipt of E-mail via POP3: Enabled
 Send Confirm on Request: Enabled
 Incoming E-mail cover sheet: Enabled



Connectivity Protocols (cont.)

NTP:
 Primary Server: Disabled
 0.0.0.0:123
 Alternate Server: 0.0.0.0:123
SLP: Disabled
SSDP: Enabled
FTP: Passive
Web Services on Device:
 WS-Discovery: Disabled
 WS-Discovery Multicast: Enabled
 WS-Print: Enabled
 WS-Scan: Enabled
Web Services
 Extensible Service Registration: Enabled
 Scan Template Management: Enabled
 Xerox Secure Access: Enabled
 Session Data: Enabled
 Scan Extensions: Enabled
 Machine Configuration: Enabled
 Authen. & Author. Config: Enabled

Services

Printing

Banner Sheet: Enabled
 Sys/Start Job: Disabled
 Error Sheets: Enabled
 Paper Substitution: Enabled
 Tray Priority: 3,1,2,4,5
 Default Copies: 1
 Default Job Type: Normal Print
 Default Paper Size: x=8.50 inches, y=11.00 inches
 Default Paper Color: White
 Default 2 Sided Printing: 1 Sided
 Default Output Tray: Top Tray
 Default Output Color: Black & White
 Default Collated Sets: Enabled
 Default Stapling: No Staple
PostScript
 Level: Installed
 Version: 3
 Image Quality: 3017.102
XPS (XML Paper Specification)
 Level: Not Installed
 Version: XPS 1.0
 Image Quality: Toner Saver

PCL

Version: 6
 Pitch Size: 10.00
 Point Size: 12.00
 Font Name: Courier
 Lines Per Page: 60

Embedded Fax:

Fax Line1: Installed/Displayed
 952-921-1414
 Fax Line2: -----

Internet Fax:

Delivery Confirm Timeout: Not Displayed
 Confirmation Sheet: 10800 seconds
 Activity Report: Errors Only
 Accept Email with no Attach: Enabled
 Disabled

Server Fax:

Confirmation Sheet: Not Displayed
 Delay Start: Errors Only
 Repository Protocol: Disabled
 Repository Server: FTP
 Repository Document Path: 0.0.0.0
 /

Workflow Scanning:

Confirmation Sheet: Displayed
 Default Repository Protocol: Errors Only
 Default Repository Server: FTP
 Default Repository Path: 13.135.149.15:21
 /InboxMFD
 Default Repository Login Credentials: System
 Alt1 Repository Protocol: FTP
 Alt1 Repository Server: 0.0.0.0:21
 Alt1 Repository Document Path: /
 Alt1 Repository Login Credentials: System
 Template Pool Protocol: FTP
 Template Pool Server: 13.135.149.15:21
 Template Pool Path: /TemplatePoolMFD/21da3454-47b2-43bb-98...

Services (cont.)

Email:
 Default From Address: Displayed
 Default From Name: xerox.scan2email@xerox.com
 Confirmation Sheet: Enabled
 Auto Send to Self: Enabled
 E-mail Security: Disabled
Scan to Mailbox:
 View Mailboxes by Default: Disabled
 Storage Capacity (MB): 28161.48 MB
 Storage Used (MB): 1602.60 MB
 Cleanup of Public Folders: Enabled
 Cleanup of Created Folders: Enabled
 Cleanup Time: Hourly
Scan to Home:
 Friendly Name: Enabled/Displayed
 Template Name: Scan2Home
 Auto Create Subdir: Enabled
 Append User Name to Path: Enabled
 Auto Create User Name Dir: Enabled
Scan To: Displayed
Print From: Displayed
 Saved Jobs for Reprint: Enabled
 Print From USB: Enabled
 Print From Mailbox: Disabled

Accounting

Accounting Mode: None
 Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Locally on the Device
 Services Pathway: Unlocked
 Job Status Pathway: Unlocked
 Machine Status Pathway: Unlocked
 Web UI Authentication: Locally on the Device
 Authorization: Locally on the Device
 Retrieve E-mail from LDAP: Enabled
Authentication Server: Disabled

Authentication Server:

Kerberos Primary Realm: 0.0.0.0:88
 Kerberos Primary Address:
 Kerberos Alt 1 Realm: 0.0.0.0:88
 Kerberos Alt 1 Address:
 SMB NT Domain:
 SMB Alt 1 NT Domain:
 NDS Default Tree:
 NDS Default Context:
 NDS Alt 1 Tree:
 NDS Alt 1 Context:
 Smartcard Ctrl Server:
 Smartcard Ctrl Domain:
 SmartCard OCSP URL:

Xerox Secure Access:

Secure Access Server: Enabled
 Secure Access Path: 0.0.0.0:443

Audit Log:

IP Sec: Enabled
 IP Filtering: Disabled
 802.1x: Disabled
 Authentication Method: EAP-MD5

Image Overwrite

Immediate: Installed/disabled
 Scheduled: Disabled
 Scheduled Frequency: Monthly

Encryption

FIPS 140-2: Disabled
 User Data Encryption: installed/enabled

McAfee Embedded Control

Enhanced Security: Enabled
 Integrity Control: Disabled

Media Trays

Tray 1: Plain, White and Letter (8.5 x 11")
 Tray 2: Plain, White and Letter (8.5 x 11")
 Tray 3: Plain, White and A4 (210 x 297 mm)
 Tray 4: Plain, White and A4 (210 x 297 mm)
 Tray 5 (Bypass): Cardstock, White and x=5.98 inches, y=5.20...



Common User Data

Machine Name: USA4320-448-WC5865
 IP Address: 13.243.33.24
 Machine Serial Number: EX9282549
 Fax Line1: 952-921-1414
 System Software Version: 071.190.103.35100
 Machine URL: http://13.243.33.24

Machine Profile

Machine Name: USA4320-448-WC5865
 Machine Serial Number: EX9282549
 Xerox Asset Tag:
 Customer Asset Tag:
 Service Phone Number:
 Customer Support Phone Number:
 Supplies Phone Number:
 System Administrator: System Administrator name not set
 Machine Location: USA 4320 Bloomington, MN

Machine Hardware

Fax Card: present
 Extended Fax Card: not present
 Fax Card Memory Size: 985 MB
 Foreign Interface Card: not present
 Net Controller RAM: 2048 MB
 Net Controller Disk Size: used=4555MB/total=160041MB
 EPC Memory Size: 512 MB
 Image Disk: present
 Finisher Type: Office Finisher (LCSS) with Hole Punch
 Finisher Punch: Present
 Finisher Folder: not present

General Setup

Low Power Mode Timer: 60 minutes
 Sleep Mode Timer: 120 minutes
 Energy Saver Mode: Job Activated
 SMart eSolutions: Enrolled
 SMart eSolutions Trans. Time: 21:05
 E-mail Alerts: Enabled
 Service Plan: Metered
 Startup Config Report: Enabled
 GMT Offset: -6:00

Software Versions

System Software: 071.190.103.35100
 Network Controller: 071.193.35110.LL
 User Interface: 071.193.35110
 Marking Engine: 096.046.000
 Copy Controller: 071.193.35110
 Document Feeder: 110.011.010
 Finisher: 003.057.000
 Fax: 003.010.032
 Copy Controller OS: 071.003.35110
 Network Controller OS: 071.003.35110
 Scanner: 002.071.000
 Software Upgrade: 190.116.00252

Machine Upgrades

Last Successful Upgrade: Enabled
 December 23, 2013 11:24:34
 Scheduled Auto Upgrades: Disabled
 Auto Upgrade Start Time: Daily
 Auto Upgrade Server: 0.0.0.0:21

Connectivity Physical Connections

USB Settings

USB Connection Mode: Software Tools
 Print Timeout: 5 seconds

Wired:

Ethernet MAC Address: Enabled
 Ethernet Speed/Duplex Setting: 9c:93:4e:1b:7e:9d
 auto

Wireless:

SSID: Disabled
 Security Mode:
 Encryption Algorithm:
 Status:

Connectivity Protocols

NetWare:

Print Server Name: Disabled
 XRX9C934E1B7E9D
 NDS Tree: Xerox_DS_Tree
 NDS Context: Xerox_DS_Context
 NDS Server: 0.0.0.0
 Novell Filing Transport: IP
 IPX Frame Type: ethernet_auto
 IPX External Number:

AppleTalk:

Name: Disabled
 XRX9C934E1B7E9D
 Zone:

Connectivity Protocols (cont.)

TCP/IPv4:

Enabled
 IP Address: 13.243.33.24
 Subnet Mask: 255.255.255.0
 Router/Gateway: 13.243.33.1
 Automatic Addressing: STATIC
 DHCP Server: 13.135.134.15
 DHCP Lease Expiration: Mon Jul 1 10:59:41 2013 CDT
 BOOTP Broadcast: Disabled
 Self Assigned Address State: Enabled
 Self Assigned Address: 169.254.70.219

TCP/IPv6:

Link Local Address:
 Use Router Supplied Prefix: Enabled
 Stateless Global Address 1:
 Stateless Global Address 2:
 Manual Address: ::
 DHCP Addressing: Use DHCP as directed by a router
 DHCP Address:
 Default Gateway:

DNS Settings:

Requested Host Name: USA4320-445-WC5865
 Verified Host Name:
 Requested Domain Name: na.xerox.net
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registra... Disabled
 Primary DNS Server: 13.135.130.15
 Alternate DNS Server 1: 13.135.177.15
 Alternate DNS Server 2: 13.151.178.15
 Connection Timeout: 5
 Append Device Domain: Enabled
 Append Parent Domains: Disabled
 DNS Domain Search List: na.xerox.net.
 Prefer IPv6 DNS over IPv4: Disabled

HTTP:

Enabled
 Port Number: 80
 Force Traffic over SSL: Yes
 Secure HTTP Port Number: 443
 Proxy Server: Enabled
 Proxy Server Address: proxywest.idns.xerox.com:8000
 IPP Network Path: https://13.243.33.24:443

SNMP

SNMP v1/v2: Enabled
 SNMP v3: Enabled

LPR/LPD:

Port Number: 515
 PDL Switching: Disabled
 PDL Banner Override: Disabled
 Raw IP Printing: Disabled
 Port Number 1: 9100
 Bidirectional: Disabled
 End of Job Timeout: 300
 PDL Switching: Disabled

LDAP

Primary LDAP Address: ldapsna.idns.xerox.com:389
 Alternate LDAP Address: ldapseu.idns.xerox.com:389
 Search Directory Root: DC=na,DC=xerox,DC=net
 Login Credentials: System
 SSL: Disabled
 LDAP Referrals: Disabled
 Query On: Surname and Given Name Fields
 Default Login Context:
 Address Book Filter State: Disabled
 Address Book Filter:
 User ID Query Filter State: Disabled
 User ID Query Filter:

SMTP

SMTP Server: forwarder.mail.xerox.com:25
 E-mail Address: xerox.scan2email@xerox.com
 Max Message Size (KB): 10240
 Number of Fragments: 1
 Total Job Size (KB): 300000
 Job Splitting Boundary: Page Boundary
 Credentials for Auto E-mails: None
 Credentials for Walkup User: None

POP3

POP3 Server: 0.0.0.0:110
 Receipt of E-mail via POP3: Enabled
 Send Confirm on Request: Enabled
 Incoming E-mail cover sheet: Enabled

Connectivity Protocols (cont.)

NTP: Disabled
 Primary Server: 0.0.0.0:123
 Alternate Server: 0.0.0.0:123
SLP: Disabled
SSDP: Enabled
FTP: Passive
Web Services on Device:
 WS-Discovery: Disabled
 WS-Discovery Multicast: Enabled
 WS-Print: Enabled
 WS-Scan: Enabled
Web Services
 Extensible Service Registration: Enabled
 Scan Template Management: Enabled
 Xerox Secure Access: Enabled
 Session Data: Enabled
 Scan Extensions: Enabled
 Machine Configuration: Enabled
 Authen. & Author. Config: Enabled

Services

Printing
 Banner Sheet: Enabled
 Sys/Start Job: Disabled
 Error Sheets: Enabled
 Paper Substitution: Enabled
 Tray Priority: 3,1,2,4,5
 Default Copies: 1
 Default Job Type: Normal Print
 Default Paper Size: x=8.50 inches, y=11.00 inches
 Default Paper Color: White
 Default 2 Sided Printing: 1 Sided
 Default Output Tray: Top Tray
 Default Output Color: Black & White
 Default Collated Sets: Enabled
 Default Stapling: No Staple
PostScript
 Level: Installed
 Version: 3
 Image Quality: 3017.102
XPS (XML Paper Specification)
 Level: Not Installed
 Version: XPS 1.0
 Image Quality: Toner Saver
PCL
 Version: 6
 Pitch Size: 10.00
 Point Size: 12.00
 Font Name: Courier
 Lines Per Page: 60
Embedded Fax: Installed/Displayed
 Fax Line1: 952-921-1414
 Fax Line2: -----
Internet Fax: Not Displayed
 Delivery Confirm Timeout: 10800 seconds
 Confirmation Sheet: Errors Only
 Activity Report: Enabled
 Accept Email with no Attach: Disabled
Server Fax: Not Displayed
 Confirmation Sheet: Errors Only
 Delay Start: Disabled
 Repository Protocol: FTP
 Repository Server: 0.0.0.0
 Repository Document Path: /
Workflow Scanning: Displayed
 Confirmation Sheet: Errors Only
 Default Repository Protocol: FTP
 Default Repository Server: 13.135.149.15:21
 Default Repository Path: /InboxMFD
 Default Repository Login Credentials: System
 Alt1 Repository Protocol: FTP
 Alt1 Repository Server: 0.0.0.0:21
 Alt1 Repository Document Path:
 Alt1 Repository Login Credentials:
 Template Pool Protocol: System
 Template Pool Server: FTP
 Template Pool Path: 13.135.149.15:21
 Template Pool Path: /TemplatePoolMFD/21da3454-47b2-43bb-98...

Services (cont.)

Email: Displayed
 Default From Address: xerox.scan2email@xerox.com
 Default From Name:
 Confirmation Sheet:
 Auto Send to Self:
 E-mail Security:
Scan to Mailbox:
 View Mailboxes by Default:
 Storage Capacity (MB): 28161.48 MB
 Storage Used (MB): 1602.60 MB
 Cleanup of Public Folders:
 Cleanup of Created Folders:
 Cleanup Time:
Scan to Home: Enabled/Displayed
 Friendly Name: Scan2Home
 Template Name:
 Auto Create Subdir: Enabled
 Append User Name to Path: Enabled
 Auto Create User Name Dir: Enabled
Scan To: Displayed
Print From: Displayed
 Saved Jobs for Reprint: Enabled
 Print From USB: Enabled
 Print From Mailbox: Disabled

Accounting

Accounting Mode: None
 Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Locally on the Device
 Services Pathway: Unlocked
 Job Status Pathway: Unlocked
 Machine Status Pathway: Unlocked
 Web UI Authentication: Locally on the Device
 Authorization: Locally on the Device
 Retrieve E-mail from LDAP: Enabled

Authentication Server:

Kerberos Primary Realm:
 Kerberos Primary Address: 0.0.0.0:88
 Kerberos Alt 1 Realm:
 Kerberos Alt 1 Address: 0.0.0.0:88
 SMB NT Domain:
 SMB Alt 1 NT Domain:
 NDS Default Tree:
 NDS Default Context:
 NDS Alt 1 Tree:
 NDS Alt 1 Context:
 Smartcard Ctrl Server:
 Smartcard Ctrl Domain:
 SmartCard OCSP URL:

Xerox Secure Access:

Secure Access Server: Enabled
 Secure Access Path: 0.0.0.0:443

Audit Log: Enabled

IP Sec: Disabled

IP Filtering: Disabled

802.1x: Disabled

Authentication Method: EAP-MD5

Image Overwrite

Immediate: installed/disabled
 Scheduled: Disabled
 Scheduled Frequency: Monthly

Encryption

FIPS 140-2: Disabled
 User Data Encryption: installed/enabled

McAfee Embedded Control

Enhanced Security: Enabled
 Integrity Control: Disabled

Media Trays

Tray 1: Plain, White and Letter (8.5 x 11")
 Tray 2: Plain, White and Letter (8.5 x 11")
 Tray 3: Plain, White and A4 (210 x 297 mm)
 Tray 4: Plain, White and A4 (210 x 297 mm)
 Tray 5 (Bypass): Cardstock, White and x=5.98 inches, y=5.20...